

NOTES:

- 1. Protection Staking (optional)
 Stake trees with 2-4 x stakes, 1800 x 50 x 50mm, driven
 600mm into ground. Protection staking to prevent vehicle
 and/or slashers coming into contact with tree.
- 2. All services are to be verified before excavation of tree hole.
- 3. Soil test to be carried out to determine if any amelioration works are necessary to improve the soils condition.
- 4. All edging types around trees must be approved by ICC.
- 5. Supply and install non petroleum based soil-wetting agent or water crystals in accordance with Manufacturer's instructions
- 6. Soil wetting agent with fertiliser additive to be mixed through full depth of existing and imported topsoil.
- 7. Where possible allow 2.5m min clear space around mulch collar for maintenance/mowing.

REVISIONS									
		AMENDMENT		INITIALS	DATE	П	AMENDMENT	INITIALS	DATE
F						L			
E						K			
D						J			
C	Notes Altered					1			
В	Notes Altered					Н			
A	ORIGINAL ISSUE					G		-	



IPSWICH CITY COUNCIL

45 Roderick St P.O. Box 191 Ipswich QLD 4305 Tel (07) 3810 7894 Tel (07) 3810 7927 Fax (07) 3810 7950



STANDARD DRAWING

PLANTING - POTTED/BAGGED TREE IN GRASSED AREA PARKS

SP.05

REV: C DRAWER: 100